



MATERIAL SAFETY DATA SHEET

Print date: 27-Aug-2008 Revision Number: 1 Revision date: 27-Aug-2008

1. IDENTIFICATION OF THE SUBSTANCE AND COMPANY

Trade Name: LEXAN* Sheet **Product ID:** 9600 -116

Product Description: Poly (bisphenol-A-carbonate) [CASRN 111211-39-3] Sheet

Product Type: Commercial Product

Recommended use: May be used as received, processed or thermoformed to produce

other articles, or as a component of other industrial products.

Company: SABIC Innovative Plastics

One Plastics Avenue Pittsfield, MA 01201 USA

(413) 448-5400 www.sabic-ip.com

Emergency Telephone Number: 800/447-4545 **Emergency Transportation/CHEMTREC (24 HOUR):** 800/424-9300

2. COMPOSITION/INFORMATION ON INGREDIENTS

This product consists primarily of high molecular weight polymers which are not expected to be hazardous.

Product Name: **9600-116** Page 1 of 7 Revision date: 27-Aug-2008

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

- · Plastic film or sheet
- Can burn in a fire creating dense toxic smoke.
- Molten plastic can cause severe thermal burns.
- Fumes produced during melt processing may cause eye, skin, and respiratory tract irritation. Severe over-exposure may result in nausea, headache, chills, and fever.
- Secondary operations, such as grinding, sanding, or sawing can produce dust which may present an explosion or respiratory hazard.

HMIS Rating	Health: 0	Flammability: 1	Reactivity: 0	
Skin Contact:		Not likely	Not likely to cause irritation.	
Eye Contact:		Resin pa to eyes.	Resin particles, like other inert materials, are mechanically irritating to eyes.	
Inhalation:		Inhalatio	Inhalation unlikely due to physical form.	
Ingestion:		Ingestion	Ingestion not likely due to physical form.	
Chronic/Carcinoge	enic Information			
Resin Issue	s:	respirato headach condens	ng fumes may cause irritation to the eyes, skin, and ry tract. In cases of severe exposure, nausea and e can also occur. Grease-like processing fume ates on ventilation ductwork, molds, and other surfaces e irritation and injury to skin.	
Aggravated Medical Conditions:		aggravat individua	MEDICAL RESTRICTIONS: There are no known health effects aggravated by exposure to this product. However, certain sensitive individuals and individuals with respiratory impairments may be affected by exposure to components in the processing vapors.	
		4. FIRST AID MEAS	SURES	
Inhalation:		be hazar or fumes	fic treatment is necessary since this material is not likely to dous by inhalation. If exposed to excessive levels of dusts r, remove to fresh air and get medica attention if cough or imptoms develop.	
Skin Contac	et:	irritation immerse to dissipa	th water and soap as a precaution. Get medical attention if develops or persists. For hot product, immediately in or flush affected area with large amounts of cold water ate heat. Cover with clean cotton sheeting or gauze and upt medical attention.	
Eye Contact	t:	any cont	tely flush with plenty of water. After initial flushing, remove act lenses and continue flushing for at least 15 minutes. If tion persists, consult a specialist.	
Ingestion:		No haza	No hazards which require special first aid measures.	
Precautions	: :	tract. If s	ng fumes inhalation may be irritating to the respiratory symptoms are experienced remove victim from the source mination or move victim to fresh air and obtain medical	

Product Name: 9600-116 Page 2 of 7 Revision date: 27-Aug-2008

advice.

5. FIRE-FIGHTING MEASURES

Explosive Limits

Storage:

upper: lower:	Not applicable Not applicable		
Suitable Extinguishing Media:	Water spray mist or foam.		
Extinguishing media which must not be used for safety reasons:	Carbon dioxide and dry chemical are not recommended because their lack of cooling capacity may permit re-ignition.		
Hazards from Combustion Products:	Fire will produce dense black smoke containing hazardous combustion products, carbon oxides, hydrocarbon fragments.		
Special Protective Equipment for Firefighters:	Do not enter fire area without proper protection including self- contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products.		
Specific Hazards:	Take precautionary measures against static discharges. Thermal decomposition can lead to release of irritating gases and vapors. Dust formed by operations such as cutting or grinding may form an explosive mixture in air.		
6. ACCIDENTAL RELEASE MEASURES			
Clean up:	Gather and store in a closed container pending a recyclability or waste disposal evaluation.		
Personal Precautions:	See section 8.		
Environmental Precautions:	Should not be released into the environment. Do not flush into surface water or sanitary sewer system.		
7. HANDLING AND STORAGE			
Handling:	Handle in accordance with good industrial hygiene and safety practice. Provide for appropriate exhaust ventilation and dust collection at machinery. Avoid dust formation. Accumulation of waste films, sheets and/or masking may create a slipping hazard.		

Keep away from heat and sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Measures to Reduce Exposure: Handle in accordance with good industrial hygiene and safety

practice. Processing fume condensate may be a fire hazard and toxic; remove periodically from exhaust hoods, ductwork, and other

surfaces using appropriate personal protection.

Hand Protection: Protective gloves

Eye Protection: Safety glasses

Respiratory Protection: When using this product at elevated temperatures, implement

engineering systems, administrative controls or a respiratory protection program (including a respirator approved for protection from organic vapors, acid gases and particulate matter) if processing fumes are not adequately controlled or operators experience symptoms of overexposure. If dust of powder are produced from secondary operations such as sawing or grinding,

use a respirator approved for protection from dust.

Skin and Body Protection: Long sleeved clothing

Hygiene Measures: When using, do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Solid

Appearance:Sheet or filmColor:VariousOdor:None or slight

Melting point/range: This product does not exhibit a sharp melting point but softens

gradually over a wide range of temperatures.

Explosive Limits

upper:Not applicablelower:Not applicable

10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions. Hazardous polymerization does not

occur.

Conditions to Avoid: Do not exceed melt temperature recommendations in product

literature.

Hazardous Decomposition Products: Processing fumes evolved at recommended processing conditions

may include trace levels of hydrocarbon fragments, phenols,

alkylphenols, diarylcarbonates.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity:

LD50/oral/rat: >5000 mg/kg, estimated LD50/dermal/rabbit: >2000 mg/kg, estimated Inhalation: Inhalation unlikely due to physical form. **Eye Contact:** Resin particles, like other inert materials, are mechanically irritating to eyes. **Skin Contact:** Not likely to cause irritation. Ingestion: Ingestion not likely due to physical form. **Chronic Toxicity:** No information available IARC: Not listed OSHA: Not regulated NTP: Not tested Remarks: The toxicological data has been taken from products of similar composition **Special Studies:** Processing fumes from similar products are not considered toxic. In acute inhalation tests, laboratory rats were exposed to processing fumes at concentrations exaggerating those that would likely occur in workplace situations. No deaths or signs of toxicity, except transient irritancy in some cases, were noted during the 6 hour fume exposure tests. There were no distinct or consistent treatment related tissue or organ changes noted in gross necropsies. 12. ECOLOGICAL INFORMATION Other information: Ecological damages are not known or expected under normal use. 13. DISPOSAL CONSIDERATIONS Waste Disposal: Recycling is encouraged. Landfill or incinerate in accordance with federal, state and local requirements. Collected processing fume condensates and incinerator ash should be tested to determine

waste classification.

US EPA Waste number: None

Transport Classification: Not regulated as hazardous for shipment, unless noted below, under current transportation guidelines. DOT ADR/RID/ADNR IMDG ICAO IATA-DGR

14. TRANSPORT INFORMATION

15. REGULATORY INFORMATION

International Inventories:

MEXICO

These film and sheet products are considered articles and thus exempt from inventory listing.

CERCLA/SARA 311/312/313:

This product is a non-hazardous article and therefore not subject to the requirements of Title III of SARA (Emergency Planning and Community Right-To-Know Act).

Canada:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS hazard class:

Non-controlled

California Proposition 65:

This product does not contain components known to the State of California to cause cancer and/or reproductive effects.

RoHS EU Directive 2002/95/EC:

This product complies with RoHS - it does not intentionally contain banned chemicals.

16. OTHER INFORMATION

LEXAN* Film is a registered trademark of SABIC Innovative Plastics

Prepared by: Product Stewardship & Toxicology

DISCLAIMER: This Material Safety Data Sheet [MSDS] information is provided based on the Hazard Communication Regulations for your region or country and for the use of the persons required to receive this information under those regulations. The information is neither designed nor recommended for any other use or for use by any other person, including for compliance with other laws. SABIC Innovative Plastics does not warrant the suitability for use of this MSDS for any other material or product not specifically identified herein. SABIC Innovative Plastics does not warrant the accuracy or authenticity of this MSDS unless it has been obtained directly from SABIC Innovative Plastics, or posted or viewed on a SABIC Innovative Plastics website. Modification of this MSDS, unless specifically authorized by SABIC Innovative Plastics, is strictly prohibited. This MSDS is based on information, that is believed to be reliable, but may be subject to change as new information becomes available. Because it is not possible to anticipate all conditions of use, additional safety precautions may be required. Since the use of this material is not under SABIC Innovative Plastics' control, each user is responsible for making its own determination as to the safe and proper handling of this material in its own particular use of this material. SABIC INNOVATIVE PLASTICS MAKES NO REPRESENTATION OR WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each user should read and understand this information and incorporate it into individual site safety programs as required by applicable hazard communication standards and regulations.

End of Material Safety Data Sheet